


















Hydraulic Pump Accessories - 3/8"

Star Part #	Picture	Description	Additional Specifications	List Price
FIT-ADP-2T-0375		Stainless steel gauge adapter 3/8 NPT female ports 4.5" length. Ideal for connecting a pressure gauge to a hydraulic circuit.		\$46.00
FIT-ELB45-0375		Elbow 90 degree 3/8" NPT with limited flow restriction, high flow rate and working pressure of 10,000 psi.		\$62.00
FIT-HEX-MXM-0375		Hex nipple 3/8" male to male with limited flow restriction, high flow rate and working pressure of 10,000 psi.		\$19.50
GAGE-ADP-0250X0375		Stainless steel 1/4" Gauge adapter. Ideal for connecting a pressure gauge to a hydraulic circuit.	3/8" ME, 3/8" FE, Female threads 1/4" NPT Gauge Port 5 1/4" length	\$39.00
GAGE-ADP-0500X0375		Stainless steel 1/2" Gauge adapter. Ideal for connecting a pressure gauge to a hydraulic circuit.	3/8" ME, 3/8" FE, Female threads 1/2" NPT Gauge Port 6" length	\$39.00
FIT-CPL-0375		Full coupler with 3/8" NPTF threads. High flow rate and working pressure of 10,000 psi		\$60.00
FIT-CPL-0375-H		Male half coupler with 3/8" NPT female threads. Hose half. High flow rate and working pressure of 10,000 psi.		\$20.75
FIT-CPL-0375-H		Female half coupler with 3/8" NPT Male threads. Ram half. High flow rate and working pressure of 10,000 psi.		\$20.75
HSH-0375-18		Lightweight hydraulic hose, 3/8" NPT. Reinforced with 2 layers of braided steel	Length 18 feet Operating pressure 10,000 psi Minimum burst pressure 20,000 psi Reinforced with 2 layers of braided steel	\$185.00
HSH-0375-2		Lightweight hydraulic hose, 3/8" NPT. Reinforced with 2 layers of braided steel	Length 2 feet Operating pressure 10,000 psi Minimum burst pressure 20,000 psi Reinforced with 2 layers of braided steel	\$57.00
HSH-0375-3		Lightweight hydraulic hose, 3/8" NPT. Reinforced with 2 layers of braided steel	Length 3 feet Operating pressure 10,000 psi Minimum burst pressure 20,000 psi Reinforced with 2 layers of braided steel	\$69.25
HSH-0375-6		Lightweight hydraulic hose, 3/8" NPT. Reinforced with 2 layers of braided steel	Length 6 feet Operating pressure 10,000 psi Minimum burst pressure 20,000 psi Reinforced with 2 layers of braided steel	\$73.25
HSH-0375-8		Lightweight hydraulic hose, 3/8" NPT. Reinforced with 2 layers of braided steel	Length 8 feet Operating pressure 10,000 psi Minimum burst pressure 20,000 psi Reinforced with 2 layers of braided steel	\$108.75
10KGAGE2500		Glycerine filled pressure gauge with range of 0-10,000 psi. 2.5" gauge 1/4" NPT brass connection 304 stainless case with plexiglass lens	Accuracy + 1.5% full scale ANSI Grade 1A Balanced Aluminum pointer w/black finish Aluminum Dial, white background, UV resistant Dial outside PSI scale, inside kPa scale Safety relief disc on top of case	\$102.00

Star Part #	Picture	Description	Additional Specifications	List Price
10KGAGE4000		Glycerine filled pressure gauge with range of 0-10,000 psi. 4.0" gauge 1/4" NPT brass connection 304 Stainless case with plexiglass lens	Accuracy + 1.5% full scale ANSI Grade 1A Balanced Aluminum pointer w/black finish Aluminum Dial, white background, UV resistant Dial outside PSI scale, inside kPa scale Safety relief disc on top of case	\$180.00
VLV-FF0250-B		Forged Brass mini valve 1/4" female x 1/4" female	108 degree operational handle Blow-out proof stem with double O rings	\$5.40
FRL-0250		Air filter-regulator, with lubricator 1/4" NPT Port 20 filter elements	Pressure adjust range 7 to 228 Max pressure 290 psi, Max flow 67.09 SCFM Oper Temp range 40F to 140F Drain Capacity 0.92 cu-in, Oil Capacity 1.83 cu-in Recommended Lubricant ISO VG-32	\$64.75
FRL-0500		Air filter-regulator, with lubricator 1/2" NPT Port 5 filter elements	Pressure adjust range 7 to 215 Max pressure 250 psi, Max flow 158.92 SCFM Oper Temp range 40F to 140F Drain Capacity 4.88 cu in, Oil Capacity 9.15 cu in Recommended Lubricant ISO VG-32	\$128.50
FRL-0375		Air filter-regulator, with lubricator 3/8" NPT Port 5 filter elements	Pressure adjust range 7 to 215 Max pressure 250 psi, Max flow 88.29 SCFM Oper Temp range 40F to 140F Drain Capacity 4.88 cu in, Oil Capacity 7.63 cu in Recommended Lubricant ISO VG-32	\$107.00
FIT-HN-0250		Hex Nipple 1/4" BRASS	Temp Range -65F to 250F Meets ASA, ASME, and SAE Specifications	\$1.15

Pneumatics 1/4" Accessories

Star Part #	Picture	Description	Additional Specifications	List Price
HSA-0125		Push-to-lock 1/4" Rubber Air Hose - Red EPDM/NR blend One High Tensile strength nylon braid reinforced	Working Pressure 300 psi Temp Range: -40F to 200F Limited Oil Resistance- Class C Color: Red	\$1.10/ft
FIT-HBM-0125A		1/4" Brass Hose barb and male pipe thread end 1/4" NPT	Usually purchased with 1/4" rubber air hose	\$1.25
FIT-HBM-0125B		1/4" Brass Hose barb and male pipe thread end 3/8" NPT	Usually purchased with 1/4" rubber air hose	\$1.25